

## **AMENDMENTS TO THE SPECIFICATION**

Please replace Paragraph [0031] with the following paragraph rewritten in amendment format:

[0031] Front housing portion 12 is further defined by a peripheral side wall including a side latch face 46 (Fig. 5), a side hinge face 48 (Fig. 4), a bottom face 50 (Fig. 7) and the top surface 44. The side hinge face 48 (best illustrated in Fig. 4) includes cutouts 54 for accommodating hinge arms ~~60A—60C~~ 120A – 120C of the hinge 17, as will be described in greater detail. A groove 64 (best shown in Fig. 9) extends around an inner edge of the top surface 44 and the side hinge face 48 of the front housing portion 12 to cooperate with a complimentary lip 66 on the rear housing portion 14 in a closed position. The bottom face 50 of the front clam shell housing portion 12 incorporates an inset portion 70, as illustrated in Figs. 7 and 9, for accommodating the frame body portions 22A – 22C while in a closed position. A ledge 68 provides vertical support for the page-like bit holders 19A and 19B when the container 10 is in a closed position. With reference to Fig. 4, the side hinge face 48 of the front housing portion 12 includes hinge posts 71 separated by void portions 72 formed thereon for accommodating hinge posts 74 of the rear housing portion 14.